



Fraunhofer

TESTED<sup>®</sup>  
DEVICE

Kemei Automation  
POD024-2POS0205-4P-CS  
**Report No. DO 2507-1646**

DUPLICATE

Statement of  
Qualification

Single product  
Particle Emission  
in Cleanroom  
(atmospheric)

Customer	Dongguan Kemei Automation Technology CO.,Ltd. CIMC Digital Technology Industrial Park, Songshan Lake Dongguan City, Guangdong Province China
Tested product	
Category:	Energy Supply
Subcategory:	Cable Systems
Product name:	KMCT Cleanroom Dedicated Cable System & Zipper Opening Pod KMCT- POD024-2P-OS, POD0205-4P-CS (manufacturing date: 6/20/2025; color: white; serial number: KMCT- 190010025678-OS-CS)

Random sampling of particle emissions (airborne) at representative sites in cleanroom under atmospheric conditions

Standards/guidelines:	ISO 14644-1, -14 The norms stated generally refer to the version valid at the time of the tests.
Test equipment:	Optical particle counter: LasAir II 110 and LasAir III 110 with measuring ranges $\geq 0.1\text{ }\mu\text{m}$ , $\geq 0.2\text{ }\mu\text{m}$ , $\geq 0.3\text{ }\mu\text{m}$ , $\geq 0.5\text{ }\mu\text{m}$ , $\geq 1.0\text{ }\mu\text{m}$ and $\geq 5.0\text{ }\mu\text{m}$
Test environment parameters:	<ul style="list-style-type: none"><li>Cleanroom Air Cleanliness Class (according to ISO 14644-1):..... ISO 1</li><li>Airflow velocity:.....0.45 m/s</li><li>Airflow pattern:..... vertical laminar flow</li><li>Room temperature: .....22 °C <math>\pm</math> 0.5 °C</li><li>Relative humidity: ..... 45 % <math>\pm</math> 5 %</li></ul>
Test procedure parameters:	<ul style="list-style-type: none"><li>Bending radius: .....r = 50 mm</li><li>Stroke length:..... s = 820 mm</li><li>Parameter Set 1:.....<math>v_1 = 0.5\text{ m/s}</math>; <math>a_1 = 1.0\text{ m/s}^2</math></li><li>Parameter Set 2:.....<math>v_2 = 1.0\text{ m/s}</math>; <math>a_2 = 2.0\text{ m/s}^2</math></li><li>Parameter Set 3:.....<math>v_3 = 2.0\text{ m/s}</math>; <math>a_3 = 4.0\text{ m/s}^2</math></li></ul>

Test result / Classification

The KMCT Cleanroom Dedicated Cable System & Zipper Opening Pod KMCT-POD024-2P-OS, POD0205-4P-CS is suitable for use under the specified test parameters (room temperature: 22 °C  $\pm$  0.5 °C; relative humidity: 45 %  $\pm$  5 %) in cleanrooms of the following Air Cleanliness Classes according to ISO 14644-1:

Test parameter(s)	Air Cleanlines Class
$v_1 = 0.5\text{ m/s}$ ; $a_1 = 1.0\text{ m/s}^2$	1
$v_2 = 1.0\text{ m/s}$ ; $a_2 = 2.0\text{ m/s}^2$	1
$v_3 = 2.0\text{ m/s}$ ; $a_3 = 4.0\text{ m/s}^2$	1
Overall result	1

Please note: Transport damages, incorrect installation, aging behavior, etc. can influence the test result.

The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

Detailed information and parameters of the test environment can be found in the Fraunhofer IPA test report.

Fraunhofer Institute for Manufacturing Engineering and Automation IPA	DO 2507-1646 Report No. first document	Stuttgart, September 24, 2025 Place, date of first document issued
Business unit Testing and Certification	-- Report No. current document	-- Place, current date
Nobelstrasse 12 70569 Stuttgart Germany	on behalf of Dr.-Ing. Frank Bürger, head of business unit Testing and Certification	